



iFD-Stator[®] 2.0

The further development of the proven iFD-Stator®

Pumps & Systems

iFD-Stator® 2.0 THE NEXT GENERATION

Characteristics and Components

As market leader and the world's biggest manufacturer of progressing cavity pumps we have often proven our know-how and innovation potential. Customer benefits and quality of our new products are always the highest priority.

The iFD-Stator[®] concept, developed in 2007, is a revolutionary breakthrough from the conventional stator design. It offers significant advantages regarding capacity, cost-savings and environmental friendliness. The iFD-Stator[®] has been accredited by the German Environmental Foundation (Deutsche Bundesstiftung Umwelt). With the introduction of the new iFD-Stator[®] 2.0 the stator can be used in an even wider range of application.

Technical Profile

- Capacity range 2 to 220 gpm / 0.5 to 50 m³/h, pressure up to 180 psi / 12 bar
- Temperature range 32°F to 194°F / 0°C to 90°C
- 01L and 02S geometry

iFD stands for

- Integration of capacity and environmental protection
- Flexibility of the sealing line through the inter-relationship between the components
- Dual system consisting of elastomer insert and clamp shell

Advantages

- Compatible with all NEMO[®] Pumps of the NM[®] series due to interchangeable dimensions
- Faster stator change due to simple opening of the stator housing, without pre-tensioning
- Long lifetime, low life cycle costs, low energy costs due to reduced starting torques
- Higher degree of efficiency
- Reliable performance through robust construction, certified elastomer quality and from a modern production process
- Certified according to ATEX
- Environmentally friendly in production and disposal





Convince yourself how simple it is to replace the iFD-Stator[®] 2.0 by watching our video!



Pay-back within the 1st maintenance cycle

Economy

The inter-relationship between the stator in the stator housing prolongs lifetime and reduces life cycle costs.

Life Cycle Costs

The reduced initial starting torque allows the selection of smaller drives which leads to the reduction in investment costs and energy consumption.

Easy to Assembly and Disassembly The two-part housing makes assembly and disassembly of the stator very easy and therefore the maintenance time is reduced.

Stator Assembly

The stator can be easily slid onto the rotor. When the stator clamp is fastened, the perfect compression fit is generated between the rotor and stator.

Reuseabilty

The stator shell is reusable and only the elastomer insert needs to be replaced. Therefore, the replacement of a stator is significantly less costly.

Patent

The unique and inovative design of iFD-Stator[®] 2.0 is registered for national and international patents.

Environmental Protection

Accredited by the German Environmental Foundation (Deutsche Bundesstiftung Umwelt) for its innovative characteristics and the diverse aspects of environmental friendliness. The NETZSCH Group is an owner-managed, international technology company with headquarters in Germany. The Business Units Analyzing & Testing, Grinding & Dispersing and Pumps & Systems represent customized solutions at the highest level. More than 4,000 employees in 36 countries and a worldwide sales and service network ensure customer proximity and competent service.

Our performance standards are high. We promise our customers Proven Excellence - exceptional performance in everything we do, proven time and again since 1873.

The NETZSCH Business Unit Pumps & Systems offers NEMO® progressing cavity pumps, TORNADO® rotary lobe pumps, NOTOS® multi-screw pumps, PERIPRO™ peristaltic pumps, macerators/grinders, metering technology and equipment custom built for challenging solutions for different applications globally.

Proven Excellence.

NETZSCH Pumps USA 119 Pickering Way EXTON, PA 19341-1393 Tel.: 610 363-8010 Fax: 610 363-0971 npa@netzsch.com

NETZSCH Pumps USA 1511 FM 1960 Road Houston, TX 77073 Tel.: 346 445-2400 npa@netzsch.com

NETZSCH Canada, Incorporated 500 Welham Road Barrie, ON L4N 8Z7 Tel.: 705 797-8426 Fax: 705 797-8427 ntc@netzsch.com





pumps-systems.netzsch.com