## NEMO® Dispenser NDP0800-03



The metering pump for all of your applications



NEMO\* Dispensers guarantee precise dosing and repeatability of highly abrasive and viscous fluids. The positive displacement, low pulsation flow conveys your product without damage to your product.


Whether your requirements call for single or 2-component meter-mix we have the size, model and solution for all of your applications.

### NEMO® Dispenser Features

- Capacity directly proportional to pump speed
- Dosing accuracy ± 1% volumetric
- Highly versatile in applications requiring robotic and servo technology
- Valve free dosing method
- Optional heating
- Perfect for shear sensitive products such as micro balloons

#### Your Benefits

- Very smooth conveyance
- Low pulsation
- Compact designs allow for easy installation in robotic applications
- Products with entrained solids are conveyed without damage
- No dripping or stringing of product
- Flow is independent of temperature or viscosity



- Low to very high viscos fluids
- Abrasive products
- Anaerobic products
- Shear and pressure sensitive products
- Dot or bead applications
- Suitable for all adhesives and sealants
- Excellent for all potting applications
- Can be used for flux and soldering pastes



# NEMO® Dispenser NDP0800-03



Dosing volume	~ 2 ml/rev.
Min. dosing quantity	0.5 ml*
Stator materials	NBR, EPDM, Viton, PTFE25%GF, (FDA Grades available)
Flow rate	13 – 400 ml/min*
Max. dispense speed	200 rpm*
Operating temperatur	e up to +248 °F / +120 °C
Max. back pressure	up to 450 psi / 30 bar*
Max. inlet pressure	145 psi / 10 bar
Weight incl. gearbox	ca. 6.6 lbs / 3 kg

\*depending on product

NETZSCH Pumps USA 119 Pickering Way Exton, PA 19341 Tel.: 610 363-8010

Fax: 610 363-0971 npa@netzsch.com

NETZSCH Pumps USA 1511 FM 1960 Road Houston, TX 77073 Tel.: 346 445-2400 npa@netzsch.com

NETZSCH Canada, Incorporated 500 Welham Road

Barrie, ON L4N 8Z7 Tel.: 705 797-8426 Fax: 705 797-8427 ntc@netzsch.com